



# SKID PLATE KTM EXC-F 450 2024


SOTTOMOTORF KTM FXC-F 450 2024





If present, remove the original skid plate by unscrewing the screws and the bushing as shown in the figure. Otherwise, just remove the screws in the frame.

Se presente, rimuovere sottomotore originale svitando le viti e la boccola come mostrato in figura. Altrimenti, rimuovere solo le viti nel telaio.



Position the Acerbis skid plate (A) and fix it using the supplied

screws (B) and the bushings (C).
Posizionare il sottomotore Acerbis (A) e fissarlo tramite le viti (B) e le boccole (C).

## **WARNING!**

Use Acerbis' products at your own risk. Check the safety of your device before you ride. Be sure that you follow the instructions for installing the Acerbis' products. Do not ride if there is missing or damaged hardware. If this is the case, take the item immediately back to your dealer. Make sure the throttle and other controls are free every time you ride. Not following these instructions and warnings could lead to interference with the controls, loss of control, and accidents. Acerbis recommends that installation must be done by a licensed mechanic and that only Acerbis' original parts are used during installation. Acerbis makes no guarantees or representations, express or implied, regarding the fitment of its product for any particular purpose. Acerbis makes no guarantees or representations, express or implied, regarding the extent to which its products protect individuals or property from injury or death or damage.

### **EUROPE**

ACERBIS ITALIA S.P.A. VIA SERIO, 37 24021 ALBINO (BG) ITALY

### U.S.A.

ACERBIS U.S.A. INC. MAIL P.O. BOX 2030 SUN VALLEY, ID 83353 SHIP 110 LINDAY CIRCLE KETCHUM, ID 83340 USA

### **UNITED KINGDOM**

ACERBIS U.K LTD UNIT 2 LUTON ENTERPRISE PARK SUNDON PARK ROAD LUTON, BEDFORDSHIRE LU3 3GU GREAT BRITAIN